§ 60.5421

1 in EPA Method 22, 40 CFR part 60, appendix A. Manufacturer's operating instructions, procedures and maintenance schedule must be available for inspection.

[77 FR 49542, Aug. 16, 2012, as amended at 78 FR 58445, Sept. 23, 2013]

§ 60.5421 What are my additional recordkeeping requirements for my affected facility subject to VOC requirements for onshore natural gas processing plants?

- (a) You must comply with the requirements of paragraph (b) of this section in addition to the requirements of §60.486a.
- (b) The following recordkeeping requirements apply to pressure relief devices subject to the requirements of §60.5401(b)(1) of this subpart.
- (1) When each leak is detected as specified in §60.5401(b)(2), a weather-proof and readily visible identification, marked with the equipment identification number, must be attached to the leaking equipment. The identification on the pressure relief device may be removed after it has been repaired.
- (2) When each leak is detected as specified in §60.5401(b)(2), the following information must be recorded in a log and shall be kept for 2 years in a readily accessible location:
- (i) The instrument and operator identification numbers and the equipment identification number.
- (ii) The date the leak was detected and the dates of each attempt to repair the leak.
- (iii) Repair methods applied in each attempt to repair the leak.
- (iv) "Above 500 ppm" if the maximum instrument reading measured by the methods specified in paragraph (a) of this section after each repair attempt is 500 ppm or greater.
- (v) "Repair delayed" and the reason for the delay if a leak is not repaired within 15 calendar days after discovery of the leak.
- (vi) The signature of the owner or operator (or designate) whose decision it was that repair could not be effected without a process shutdown.
- (vii) The expected date of successful repair of the leak if a leak is not repaired within 15 days.

- (viii) Dates of process unit shutdowns that occur while the equipment is unrepaired.
- (ix) The date of successful repair of the leak.
- (x) A list of identification numbers for equipment that are designated for no detectable emissions under the provisions of 60.482-4a(a). The designation of equipment subject to the provisions of 60.482-4a(a) must be signed by the owner or operator.

§ 60.5422 What are my additional reporting requirements for my affected facility subject to VOC requirements for onshore natural gas processing plants?

- (a) You must comply with the requirements of paragraphs (b) and (c) of this section in addition to the requirements of §60.487a(a), (b), (c)(2)(i) through (iv), and (c)(2)(vii) through (viii).
- (b) An owner or operator must include the following information in the initial semiannual report in addition to the information required in $\S 60.487a(b)(1)$ through (4): Number of pressure relief devices subject to the requirements of $\S 60.5401(b)$ except for those pressure relief devices designated for no detectable emissions under the provisions of $\S 60.482-4a(a)$ and those pressure relief devices complying with $\S 60.482-4a(c)$.
- (c) An owner or operator must include the following information in all semiannual reports in addition to the information required in §60.487a(c)(2)(i) through (vi):
- (1) Number of pressure relief devices for which leaks were detected as required in §60.5401(b)(2); and
- (2) Number of pressure relief devices for which leaks were not repaired as required in §60.5401(b)(3).

\$60.5423 What additional recordkeeping and reporting requirements apply to my sweetening unit affected facilities at onshore natural gas processing plants?

(a) You must retain records of the calculations and measurements required in 60.5405(a) and (b) and 60.5407(a) through (g) for at least 2 years following the date of the measurements. This requirement is included